

LIVE1202



PRODUCT OVERVIEW - v1

PROFESSIONAL 12-CHANNEL/2-BUS MIXER

- > 7 XLR INPUTS WITH DNA™ MICROPHONE PREAMPS
- > DYNAMIC COMPRESSION (CHANNELS 1-4)
- > 3-BAND EQ PLUS 2 AUX SENDS PER CHANNEL



SPECIFICATIONS

Mono Input Channels

Microphone inputs:	Electronically balanced, discrete input configuration
Frequency response:	20 Hz to 20 kHz, +0.5 dB
THD+N:	<0.02% at 0 dBu, 1 kHz
Gain range:	0 dB to 50 dB (Mic)
SNR:	90 dB

Line Inputs

	Electronically balanced
Frequency response:	20 Hz to 20 kHz, +0.5 dB
THD+N:	<0.03% at 0 dBu, 1 kHz
Sensitivity range:	-15 dBu to 30 dBu

Impedances

Microphone inputs:	51.1 K Ω
Channel insert return:	200 K Ω
All other inputs:	>100 K Ω
2-Track outputs:	10 K Ω
All other outputs:	20 K Ω

Equalization

High-shelving:	± 15 dB @ 12 kHz
Mid-bell (mono):	± 15 dB @ 2.5 kHz
Low-shelving:	± 15 dB @ 80 Hz
Main EQ:	9 EQ bands (63 Hz, 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, 16 kHz), ± 15 dB

DSP Section (DFX)

A/D & D/A converters:	24-bit
DSP Resolution:	24-bit
Effects:	10 DSP effects families with 10 variations available per family
Presets:	100 total
Controls:	Rotary encoder to select preset, DSP mute switch, peak LED indicator

Main Mix

Noise (bus noise):	Fader 0 dB, channels muted: -64 dBr (ref: +4 dBu) Fader 0 dB, all input channels assigned & set to unity gain: -64 dBr (ref: +4 dBu)
Phantom Power:	Mic Pin2/Pin3 and Pin1 47 \pm 2V

Power Supply

Main voltage:	USA/Canada: 100-120 VAC ~60 Hz UK/Australia: 240 VAC ~50 Hz Europe: 210-240 VAC ~50 Hz
Power consumption:	50 W
Fuse:	1.25 A
Main connection:	Standard IEC receptacle

Dimensions (w x d x h)	14.1" x 13.6" x 3.1" / 358 mm x 346 mm x 80 mm
------------------------	--

Weight	9.0 lbs. / 4.1 kg
--------	-------------------



APPLICATIONS

Small/Mid-sized PA systems
Gymnasiums, fitness centers, and dance studios
Houses of worship
Theaters
Bars, restaurants, clubs
Band and Mobile DJ systems
Special events, presentations, and weddings


FEATURES

7 XLR inputs with high- DNA™ mic preamps
Dynamic compression (Channels 1-4)
3-band EQ plus 2 aux sends per channel
60mm faders with mute switch and LED meters
USB audio connectivity with level control
100 Alesis DSP effects
Balanced XLR, balanced/unbalanced 1/4" outputs
9-band graphic EQ for main or monitor outputs
Headphone out with independent level control
USB jack to power lamps or charge mobile devices

DIMENSIONS



CONNECTORS



LIVE1202

altoprofessional.com

ALTO
PROFESSIONAL

All information subject to change. Page 2