



TX18S

900-WATT 18-INCH DSP-ENHANCED
POWERED SUBWOOFER

APPLICATIONS

- Medium to large scale venues
- Rehearsal studios
- Bar or Nightclubs
- House of worship

FEATURES

- 900W Ultra-Efficient Class-D Power Amplifier
- 18-inch high-output woofer with 3-inch voice coil
- DSP-based EQ and protection.
- Music and Live EQ voicings
- Selectable Low Pass Filter (80Hz / 100Hz / 120Hz)
- Polarity Reverse
- (2) XLR +1/4-inch combo line inputs
- (2) balanced XLR line outputs
- Ported design with Full metal grille for premium style and protection
- Rugged, internally braced front-ported MDF cabinet w/36mm pole socket
- Rugged, splatter-spray finish always looks good, even with heavy use
- Side handles

SPECIFICATIONS

LF Driver	18" woofer / 3" VC
Power Amp	450W RMS / 900W peak class-D
Frequency Response	36Hz – 115kHz (-3dB)
Max SPL	126dB @ 1m
Connectors	(2) XLR/TRS combo inputs, (2) balanced XLR line outputs, (1) IEC power cable input
Power Connection	IEC
Voltage	100-120 220-240 VAC, 50/60 Hz
DSP LPF	80Hz / 100Hz / 120Hz @24dB per octave
Handles	2 side handles
Enclosure	Internally braced front-ported MDF cabinet with black splatter spray, metal grille, rubber feet
Mounting	36 mm pole socket
Dimensions	23" x 23" x 23" (585 x 585 x 585mm)
Weight	87.7lbs / 39.8kg